

SUPPORT ACCESSORIES CASTERS

CASTER	CODE/CAPACITY PER PAIR	CASTER	CODE/CAPACITY PER PAIR
4" DIA. RUBBER RIGID	4RR/600 lbs.	4" DIA. RUBBER SWIVEL W/TOE BRAKE	4RSB/-
4" DIA. STEEL RIGID	4SR/700 lbs.	6" DIA. RUBBER RIGID	6RR/1120 lbs.
4" DIA. V-GROOVE RIGID	4VR/-	6" DIA. STEEL RIGID	6SR/1150 lbs.
4" DIA. RUBBER SWIVEL	4RS/600 lbs.	6" DIA. RUBBER SWIVEL	6RS/1120 lbs.
4" DIA. STEEL SWIVEL	4SS/700 lbs.	6" DIA. STEEL SWIVEL	6SS/1150 lbs.
4" DIA. V-GROOVE SWIVEL	4VS/-	6" DIA. STEEL SWIVEL W/BRAKE	6SSB/-
FLOORLOCK FOR 4" CASTER	-	FLOORLOCK FOR 6" CASTER	-

CASTERS FOR LIGHT DUTY CONVEYORS SLC-5-16-4RSBF

SLC-(elevation code)-(between frames*)-(caster model**)-(floorlock@)

*Specify 10", 16" or 22" between frames only. Model SLC is suited specifically for wheel conveyors and 138 gravity series.

**See chart for caster model number.

@Specify F if floorlock required.

CASTERS FOR MEDIUM DUTY CONVEYORS SMC-4-13-4RSBF

S (medium or heavy duty*) C-(elevation code)-(between frames)-(caster model**)-(floorlock@)

*Specify M for medium duty supports and H for heavy duty supports.

**See chart for caster model number.

@Specify F if floorlock required.

SPECIFICATIONS

CASTERS: 4" dia. or 6" dia., steel or rubber, swivel or rigid, V-groove casters; floor locks, wheel brakes available. Two casters supplied per support with enlarged mounting plate welded to legs.

CAPACITY: Up to 1150 lb. caster capacity. Consult factory for heavy duty casters.

OPTIONAL: Angle track for V-groove.



■ 24 hour shipment

■ 2 week shipment

KNEE BRACE AND ADJUSTABLE SUPPORT BRACKET

MEDIUM DUTY KNEE BRACE MODEL KB CODE NO.	HEAVY DUTY KNEE BRACE MODEL HKB CODE NO.	POLYTIER KNEE BRACE PKB CODE NO.	NOSE-OVER KNEE BRACE MODEL NOKB CODE NO.
2	2	-	6
4	4	4	-
6	6	6	-
8	8	8	-
10	10	10	-
12	12	-	-
-	14	-	-

SPECIFY KNEE BRACE MODEL NUMBER

KB-6

(model number*)-(code number)

*Specify KB (medium duty for SL or SM supports), HKB (heavy duty for SH or SS supports), PKB (for polytier supports) or NOKB (for mounting on nose-over).

ADJUSTABLE SUPPORT BRACKET C-3

C-3

C-3

SPECIFICATIONS

KNEE BRACE: Available in 3 styles; Model KB (10 ga.) for SL and SM supports, Model HKB (7 ga.) for SH and SS supports and Model PKB (10 ga.) for polytier supports.

C-3 ADJUSTABLE SUPPORT BRACKET:

10 ga. construction on support Models SL and SM; 7 ga. on Model SH.



KB knee braces add strength to permanent supports and stability in portable applications. C-3 adjustable support bracket allows support to be attached easily to conveyor.



■ 24 hour shipment

