

# SUPPORTS

## MODEL SL LIGHT DUTY PERMANENT SUPPORTS



**MODEL SL**  
1500 lbs. support capacity

### SPECIFICATIONS

**CONSTRUCTION:** 12 ga. inside and outside channel assemblies; C-3 plates are 10 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

**WIDTHS:** 24 HR shipments include SL in 10", 16" & 22" BF ONLY.

### LIGHT DUTY SUPPORTS MODEL NUMBER SL-6-10

SL-(elevation code)-(between frames\*)  
\*Specify 10", 16" or 22" between frames which is available for 12", 18" and 24" OAW conveyors ONLY and is suited specifically for wheel conveyors and 138 gravity series.

ELEVATION CODE	HEIGHT ADJUSTMENT MIN. (TOP OF SUPPORT)	HEIGHT ADJUSTMENT MAX. (TOP OF SUPPORT)	10"-22" BF WEIGHT (lbs.)
1	7-1/4"	10-1/4"	11
2	10-1/4"	13-1/4"	13
3	13-1/4"	16-1/4"	15
4	16-1/4"	22-1/4"	17
5	20-1/4"	26-1/4"	22
6	24-1/4"	36-1/4"	24
7	34-1/4"	46-1/4"	28
8	46-1/4"	58-1/4"	35
9	58-1/4"	70-1/4"	39
10	70-1/4"	82-1/4"	43
11	80-1/4"	92-1/4"	47
12	92-1/4"	104-1/4"	51

■ 24 hour shipment

## MODEL SM MEDIUM DUTY PERMANENT SUPPORTS

ELEVATION CODE	HEIGHT ADJUSTMENT MIN. (TOP OF SUPPORT)	HEIGHT ADJUSTMENT MAX. (TOP OF SUPPORT)	7-21" BF WT. (lbs.)	22-27" BG WT. (lbs.)	28-39" BF WT. (lbs.)	40-51" BF WT. (lbs.)
1	7-1/4"	10-1/4"	10	11	15	17
2	10-1/4"	13-1/4"	12	13	16	18
3	13-1/4"	16-1/4"	14	15	18	20
4	16-1/4"	22-1/4"	16	17	20	22
5	20-1/4"	26-1/4"	21	23	30	33
6	24-1/4"	36-1/4"	23	25	32	36
7	34-1/4"	46-1/4"	27	29	36	39
8	46-1/4"	58-1/4"	34	36	47	53
9	58-1/4"	70-1/4"	38	40	52	57
10	70-1/4"	82-1/4"	42	44	56	61
11	80-1/4"	92-1/4"	46	48	60	65
12	92-1/4"	104-1/4"	50	52	64	69

### MEDIUM DUTY SUPPORTS MODEL NO. SM-5-39

SM-(elevation code\*)-(between frames)  
\*See chart at left

### MINIMUM ELEVATION SUPPORTS MODEL NO. SMO-1-17

SMO-(elevation code\*)-(between frames)  
\*See chart below.

### SPECIFICATIONS

**CONSTRUCTION:** 12 ga. inside and outside channel assemblies; C-3 plates are 10 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

**WIDTHS:** 24 HR shipments include 7", 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47" & 51" BF.

MIN. ELEVATION MEDIUM DUTY ELEVATION CODE	HEIGHT ADJ. RANGE (TOP OF SUPPORT)	UP TO 27" BF WT. (lbs.)	27"-51" BF WT. (lbs.)
1	3-1/2" — 4-1/8"	10	17
2	4-1/8" — 4-3/4"	10	17
3	4-3/4" — 5-3/8"	10	17
4	5-3/8" — 6"	10	17
5	6" — 6-5/8"	10	17
6	6-5/8" — 7-1/4"	10	17



**MODEL SM**  
1500 lbs. support capacity

■ 24 hour shipment ■ 2 week shipment

