

SUPPORTS

MODEL SH HEAVY DUTY PERMANENT SUPPORTS

ELV. CODE	HEIGHT ADJ. MIN. (TOP OF SUPPORT)	HEIGHT ADJ. MAX. (TOP OF SUPPORT)	7-21" BF WT. (lbs.)	22-27" BF WT. (lbs.)	28-39" BF WT. (lbs.)	40-51" BF WT. (lbs.)
1	6-1/4"	7-3/4"	12	13	17	18
2	7-3/4"	10-3/4"	13	14	18	19
3	10-3/4"	13-3/4"	14	15	19	20
4	13-3/4"	16-3/4"	17	18	21	23
5	16-3/4"	19-3/4"	18	19	22	24
6	19-3/4"	25-3/4"	22	24	31	35
7	25-3/4"	21-3/4"	27	29	37	40
8	31-3/4"	43-3/4"	31	33	40	44
9	43-3/4"	55-3/4"	40	42	53	59
10	55-3/4"	67-3/4"	45	47	58	64
11	67-3/4"	79-3/4"	50	52	64	69
12	79-3/4"	91-3/4"	57	59	70	75

HEAVY DUTY SUPPORTS MODEL NO. SH-4-51

SH-(elevation code*)-(between frames)
*See chart at left.



MODEL SH
3000 lbs. support capacity

SPECIFICATIONS

CONSTRUCTION: 10 ga. inside and outside channel assemblies; C-3 plates are 7 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

WIDTHS: 24 hour shipment includes 7", 9", 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47", 51" BF only; 54", 57" and 63" BF available in models SH-1 to SH-6.

MODEL SHO HEAVY DUTY

ELEVATION CODE	HEIGHT ADJ. RANGE (TOP OF SUPPORT)	UP TO 27" BF WT. (lbs.)	28"-51" BF WT. (lbs.)
1	3-1/2" — 4-1/8"	13	18
2	4-1/8" — 4-3/4"	13	18
3	4-3/4" — 5-3/8"	13	18
4	5-3/8" — 6"	13	18
5	6" — 6-5/8"	13	18

MINIMUM ELEVATION SUPPORTS MODEL NO. SH0-5-33

SH0-(elevation code*)-(between frames)
*See chart below left.

HEAVY DUTY STRUCTURAL SUPPORTS

■ 24 hour shipment



MODEL SS
6000 lbs. support capacity

STRUCTURAL SUPPORTS MODEL NUMBER SS-4-31

SS-(elevation code)-(between frames)

3530 STRUCTURAL SUPPORTS MODEL NO. SS3530-6-45

SS3530-(elevation code)-(between frames)



MODEL SS3530
12000 lbs. support capacity

MODEL SS ELEV. CODE	HT. ADJ. RANGE (TOP OF SUPPORT)	7"-23" BF WT. (lbs.)	24"-51" BF WT. (lbs.)	52"-63" BF WT. (lbs.)	MODEL SS ELEV. CODE	HT. ADJ. RANGE (TOP OF SUPPORT)	7"-23" BF WT. (lbs.)	24"-51" BF WT. (lbs.)	52"-63" BF WT. (lbs.)	MODEL SS3530* ELEV. CODE	HT. ADJ. RANGE (TOP OF SUPPORT)
1	7-1/4" — 10-1/4"	26	39	44	13	99-1/2" — 114-1/2"	154	191	207	1	8-3/8" — 10-5/8"
2	10-1/4" — 13-1/4"	31	44	50	14	102-1/2" — 117-1/2"	160	198	214	2	10-3/8" — 13-1/8"
3	13-1/4" — 16-1/4"	35	47	53	15	105-1/2" — 120-1/2"	163	201	217	3	12-7/8" — 18-1/8"
4	16-1/4" — 22-1/4"	40	53	59	16	108-1/2" — 126-1/2"	166	204	220	4	17-7/8" — 23-3/8"
5	20-1/4" — 26-1/4"	45	58	64	17	112-1/2" — 130-1/2"	170	208	224	5	23-1/8" — 28-5/8"
6	24-1/4" — 36-1/4"	56	69	75	18	116-1/2" — 140-1/2"	180	218	234	6	28-3/8" — 33-7/8"
7	34-1/4" — 46-1/4"	83	108	119	19	126-1/2" — 150-1/2"	189	227	243	7	33-5/8" — 39-1/8"
8	46-1/4" — 58-1/4"	92	117	128	20	138-1/2" — 162-1/2"	200	238	254	8	38-7/8" — 44-3/8"
9	58-1/4" — 70-1/4"	105	130	141	21	150-1/2" — 174-1/2"	211	249	265	-	-
10	70-1/4" — 82-1/4"	116	141	152	22	162-1/2" — 186-1/2"	222	260	276	-	-
11	80-1/4" — 92-1/4"	136	174	191	23	172-1/2" — 196-1/2"	231	269	285	-	-
12	92-1/4" — 104-1/4"	147	185	202	24	184-1/2" — 208-1/2"	241	279	295	-	-

SPECIFICATIONS

BF'S: 24 hr. ship includes 7", 9", 11", 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 35", 37", 39", 43", 45", 47", 51" BF only; 54", 57" & 63" BF 2 wk. ship.

*Model SS3530 adjustable in 1/4" increments ONLY.

■ 24 hour shipment ■ 2 week shipment

